


RECOMMEND P.C.B. LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION	PDS. 1	PDS. 2	PDS. 3
DN	■	□	□
DN	□	■	□
DN	□	□	■
2-1	DN	OFF	OPEN
2-3	DN	DN	DN

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: 0.0=±0.4  
0.00=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. TRAVEL TO MAKE: 2.16mm
  5. RATING: 6 Amps @120VAC or 28VDC; 3 Amps @250VAC.

**E-SWITCH®**

B	10913	TITLE: SSP-3 WAS SSP-2	8/29/00	PML
A		RELEASED FOR PRODUCTION		
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		500 SSP-3 S1 M7 Q E A		SCALE	2:1	DATE	8/29/00	DR	PML	DWG	TS11205	REV	B
-------	--	-----------------------	--	-------	-----	------	---------	----	-----	-----	---------	-----	---

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED