


Cylinder Type PAS Capacitor(High Voltage Type)[LA series]

PAS1020LA2R3475



■ Features

- Item Summary
4.7F, 2.3V, ϕ 10.0x20.0mm
- Lifecycle Stage
Mass Production

■ Products characteristics table

| | |
|-------------------------------|--------------------------|
| Nominal Capacitance | 4.7 F |
| Max. Usable Voltage | 2.3 V (at -25 to +60 °C) |
| Initial Internal Resistance | 0.3 Ω max |
| Initial Capacitance | 4.7 F \pm 20% |
| Operating Temp. Range | -25 to +60 °C |
| RoHS2 Compliance (10 subst.) | Yes |
| REACH Compliance (173 subst.) | Yes |
| Soldering | Wave |

■ External Dimensions

| | |
|-------------|--------------------------|
| Dimension D | ϕ 10.0 \pm 0.5 mm |
| Dimension L | 20.0 \pm 2.0 mm |
| Dimension d | Typ ϕ 0.6 mm |
| Dimension P | 5.0 \pm 0.5 mm |

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.