

	Circumference	
Band Size	Min.	Max.
Small	5.5" (140mm)	9" (229mm)
Medium	6" (152mm)	11" (279mm)
Large	7" (178mm)	12" (305mm)

ltem	Band Size	Coil Cord
<u>19886</u>	Small	Not Included
<u>19887</u>	Medium	Not Included
<u>19888</u>	Large	Not Included
<u>19889</u>	Small	6' ( <u>19880</u> )
<u>19890</u>	Medium	6' ( <u>19880</u> )
<u>19891</u>	Large	6' ( <u>19880</u> )
<u>19892</u>	Small	12' ( <u>19881</u> )
<u>19893</u>	Medium	12' ( <u>19881</u> )
<u>19894</u>	Large	12' ( <u>19881</u> )

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a <u>Desco MagSnap™ 360 Coil Cord</u> (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

All tolererances are 10% unless otherwise specified. Specifications and procedures are subject to change without notice.



U.S. Patent Pending

## MAGSNAP 360<sup>™</sup> DUAL-WIRE METAL EXPANSION WRISTBAND





