



192-10010 Article Number:

Snapper Hose Clamp, .24"-.26" Bundle Diameter, PA66GF13, Black, 100/pkg Description:

| Base Data             |                                 |  |
|-----------------------|---------------------------------|--|
|                       |                                 |  |
|                       | Local Order Number              | SNP1GHS0C2   |
|                       | Туре                            | SNP1   |
|                       | Color                           | Black (BK)   |
|                       | Features and benefits           | <ul> <li>Designed for quick, ratcheted installation and can be released and reused.</li> <li>Heat stabilized material is suitable for high temperature applications.</li> </ul>  |
|                       | Quantity Per                    | bag  |
|                       | Product Description             | HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes. |
|                       | Short Description               | Snapper Hose Clamp, .24"26" Bundle Diameter, PA66GF13, Black, 100/pkg  |
| Product<br>Dimensions |                                 |  |
|                       | Fixation Method                 | Plug-in mounting   |
|                       | Variant                         | Closed   |
|                       | Width W2 (Imperial)             | 0.149"   |
|                       | Width W2 (Metric)               | 3.8mm  |
|                       | Bundle Diameter Min. (Imperial) | 0.3"   |
|                       | Bundle Diameter Min. (Metric)   | 6.0mm  |
|                       | Bundle Diameter Max. (Imperial) | 0.27"  |
|                       | Bundle Diameter Max. (Metric)   | 6.8mm  |
|                       | Diameter Min. (Imperial)        | 0.237"   |
|                       | Diameter Min. (Metric)          | 6.02mm   |
|                       | Diameter Max. (Imperial)        | 0.263"   |
|                       | Diameter Max. (Metric)          | 6.68mm   |
|                       | Nominal Diameter (Imperial)     | 1/4"   |
|                       | Nominal Diameter (Metric)       | 6mm  |

generated on: 4/29/2017

## 192-10010



| Product<br>Dimensions          | Wall Thickness WT (Imperial) | .04"   |
|--------------------------------|------------------------------|--|
|                                | Wall Thickness WT (Metric)   | 1.0mm  |
| Material and<br>Specifications |                              |  |
|                                | Material                     | Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%) |
|                                | Material Shortcut            | PA66GF13   |
|                                | Flammability                 | UL 94 HB   |
|                                | Operating Temperature        | -40°F to +221°F (-40°C to +105°C)                                      |
|                                | REACH Compliant (Article 33) | Yes  |
|                                | ROHS Compliant               | Yes  |
| Logistic and<br>Packaging      |                              |  |
|                                | Package Quantity (Imperial)  | 100  |
|                                | Package Quantity (Metric)    | 100Pieces  |
|                                | Customs Number(Schedule B)   | 3926909987   |
|                                | Content Unit (BMEcat)        | pieces   |
|                                | Weight (Metric)              | 0.12kg   |

generated on: 4/29/2017