

151-29000

Article Number: 151-29000



Description: Adhesive Base, .63" x .63", .1" Max Tie Width, .11" Hole Dia, PA66/SR T50, Black, 100/pkg

Base Data	
Local Order Number	MB2.5A0C2
Type	MB2.5A
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• For use with 18 pound cable ties to provide stability when securing bundles.</li> <li>• Secures with rubber based adhesive backing and/or two or four screws.</li> <li>• 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
Short Description	Adhesive Base, .63" x .63", .1" Max Tie Width, .11" Hole Dia, PA66/SR T50, Black, 100/pkg
Product Dimensions	
Length L (Imperial)	0.625"
Length L (Metric)	15.9mm
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	0.625"
Width W (Metric)	15.9mm
Cable Tie Width Max. (Imperial)	0.1"
Cable Tie Width Max. (Metric)	2.54mm
Height H (Imperial)	0.16"
Height H (Metric)	4.1mm
Mounting Hole Diameter D (Imperial)	0.11"
Mounting Hole Diameter D (Metric)	2.8 mm

151-29000



Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Adhesive	Synthetic rubber with base of polyethylene foam
	Adhesive Operating Temperature	-4°F to +122°F (-20°C to +50°C)
	Flammability	UL 94 V2 (excluding adhesive)
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987