

# Universal Reversible USB 2.0 Hi-Speed Cable (Reversible A to 5Pin Mini B M/M), 6-ft.

MODEL NUMBER: UR030-006-SLIM





#### Description

Tripp Lite's UR030-006-SLIM 6-ft. USB 2.0 A to 5-Pin Mini-B device cable features a Super Slim design that is 25% thinner than standard USB Mini-B cables. It also includes a Universal / Reversible "A" connector, which takes the guesswork out of which way to position the "A" connector for plugging. It supports USB 2.0 data

## Highlights

- Super Slim design....25% thinner than standard USB Mini-B cables
- Universal / Reversible A connector eliminates guess-work as to connector orientation
- Supports USB 2.0 data transfer rates up to 480Mbps
- Connects to Cameras, PDA's, etc with Mini-B 5-Pin connectors

#### **System Requirements**

- Any USB device requiring a USB cable with 5-Pin Mini-B connector
- USB 2.0 performance only when used with USB 2.0 device and USB 2.0 controller

#### Package Includes

 6-ft. USB 2.0 Universal / Reversible A to 5-Pin Mini-B Super Slim Device Cable

transfer rates up to 480Mbps, and is backward compatible with USB 1.1. Connects a Digital camera, PDA, Cell Phone, or other device with a 5-Pin Mini-B connector to a USB port on a computer or hub. All Tripp Lite USB 2.0 cabling includes superior foil shielding for reliable, error-free data communications. Features nickel plated connectors and gold plated copper contacts for superior conductivity. The cable is manufactured with molded connectors and integral strain relief for extra durability and long life.

## **Features**

- Super Slim design....25% thinner than standard USB Mini-B cables
- Universal / Reversible A connector eliminates guess-work as to connector orientation
- Supports USB 2.0 data transfer rates up to 480Mbps
- Connects to Cameras, PDA's, and other devices with 5-Pin Mini-B connectors
- Premium double-shielded cables with tinned copper braid and aluminum Mylar foil
- Nickel plated connectors and gold plated copper contacts for superior conductivity.
- Molded connectors and integral strain relief for extra durability and long life.

# **Specifications**

| INPUT              |     |
|--------------------|-----|
| Cable Length (ft.) | 6   |
| Cable Length (m)   | 1.8 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| PHYSICAL                            |                             |  |
|-------------------------------------|-----------------------------|--|
| Color                               | Black                       |  |
| ENVIRONMENTAL                       |                             |  |
| Operating Temperature Range         | -10 to 75° C (14 to 167° F) |  |
| Storage Temperature Range           | -20 to 80° C (-4 to 176° F) |  |
| CONNECTIONS                         |                             |  |
| Side A - Connector 1                | REVERSIBLE USB A (MALE)     |  |
| Side B - Connector 1                | USB MINI-B 5-PIN (MALE)     |  |
| WARRANTY                            |                             |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty   |  |

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies