

151-00146



Article Number: 151-00146

Description: Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

Base Data	Local Order Number	WSM60IMHSUVH1
	Type	WSM60
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Design makes installation along frame rails fast and easy. • Using weld stud eliminates the need for grinding down painted surfaces which saves time. • Weld Stud eliminates need for stocking multiple sized metal P-Clamps which saves time and cost.
	Quantity Per	bag
	Product Description	When used in conjunction with a cable tie, the Weld Stud Mount eliminates the need for multiple sized p-clamps, nuts, and bolts, and significantly reduce time and labor. Simply weld the stud to the surface of any painted frame rail, and begin bundling with HellermannTyton cable ties. This eliminates the need in having to grind the surface in preparation.
	Short Description	Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg
	Product Dimensions	Length L (Imperial)
Length L (Metric)		33.5mm
Width W (Imperial)		1.0"
Width W (Metric)		27.2mm
Height H (Imperial)		1.0"
Height H (Metric)		27.0mm
Bundle Diameter Max. (Imperial)		6.0"
Bundle Diameter Max. (Metric)		152.4mm
Stud Size (Imperial)		0.24"
Stud Size (Metric)		6.0 mm

151-00146



Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces