

Between-Series Adapters

N to 3.5mm

N Male Plug to 3.5mm Male Plug

Model Number

ADT-2712-NM-3MM-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



N Male Plug to 3.5mm Female Jack

Model Number

ADT-2713-NM-3MF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



N Female to 3.5mm Male Plug

Model Number

ADT-2714-NF-3MM-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz


VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel



N Female to 3.5mm Female Jack

Model Number

ADT-2715-NF-3MF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz

VSWR: 1.04 @ DC-4.0 GHz

1.07 @ 4.0-8.0 GHz

1.12 @ 8.0-18.0 GHz

Impedance: 50 Ohms

Finish: Passivated Stainless Steel

