AMP 1281 (7/63)

APPLICATOR PARTS LIST

TYPE LENGTHWISE
Splice Ins. Piercing

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.
1	■ WIRE CRIMPER		
2	■ INS. CRIMPER	1	470471
3	■ ANVIL	1	377523
4	ANVIL SPACER		
5	■ SHEAR BLADE	1	377453-1
6	■ ~~REAR SHEAR~~ PLATE Feed	1	376652
7	SHEAR BLADE SPACER		
8	■ FRONT SHEAR PLATE		
9	REAR ANVIL SPACER PLT.		
10	FRONT ANVIL SPACER PLT.		
11	TOOL SPACER		
12	CRIMP SPACER		
13	FRONT STRIP GUIDE		
14	REAR STRIP GUIDE		
15	RAM	1	471057
16	TOOL HOLDER		
17	ADJ. CRIMP MOUNT		
18	ADJ. BLOCK		
19	APPLICATOR MOUNT ASSY.	1	473933
20	BASE PLATE		
21	BASE BLOCK		
22	STRIP GUIDE PLATE		
23	ANVIL HOLDER 374348	1	~~385941~~
24	AUX. ANVIL HOLDER	1	378975
25	STRIPPER	1	376945
26	STRIPPER MOUNT		
27	RETAINER PLATE		
28	STRIPPER MOUNT BRACKET		
29	STRIPPER BUSHING		
30	STOCK DRAG	1	372990
31	STOCK DRAG ~~[illegible]~~ NUT	1	21022-4
32	STOCK DRAG STUD	1	21015-8
33	STOCK DRAG SPRING 23846-7	1	~~[illegible]~~
34	STOCK DRAG ADJ. SCREW	2	372997
35	FEED FINGER HOLDER		
36	FEED FINGER 811432-1	1	~~[illegible]~~
37	FEED FINGER TIP		
38	FEED FINGER SPACER		
39	BASE CASTING	1	570238
40	GUARD 460582-1	1	~~[illegible]~~
41	~~Bracket Guard~~	~~1~~	~~[illegible]~~

NO.	DESCRIPTION	REQ.	PART NO.
42	~~Guard-End~~	~~1~~	~~377536~~
43	Spring-Slide 3/4 O.D.	1	~~[illegible]~~
44	Feed Plate Retainer	1	372998
45			
46			
47			
48			
49	Depressor-Terminal ⚠	1	692149-1
50			
51			
52			
53			
54			
55	Sq.Hd.Set Scr. Depressor	1	21077-8
56	Nut-Jam	1	22202-1
57			
58			
59			
60			
61			
62			
63			
64			
65	Tension Adj. Plate	1	374999
	MISCELLANEOUS		
66			
67			
68			
69			
70			
71			
72			

REV.	REVISION RECORD	DATE	BY	ECN
A	SUPER 671737-0	1/8/68	[illegible]	L-5345
B	ADD FEED	4/1/68	[illegible]	L-5766
C	REV PER E.C.N.	9-1-68	[illegible]	L-6095
D	REV PER ECN	4-2-77	[illegible]	L-9622
E	REV PER ECN	3-18-74	[illegible]	R-388

CRIMPING DATA			
TO APPLY TERMINAL 2-24017-7			
WIRE SIZE	CRIMP HEIGHT		
CRIMP	SIZE	TYPE	FEED
WIRE	.110	0	.266
INSUL.			
SLEEVED			
INSULATION RANGE		WIRE RANGE	
.070-.090Dia		20-16	

TERMINALS: 40638, 40771

EXPLODED VIEW: A-6010-1 A-6010-2

REMARKS:
⚠ MTS. ON TOP OF ITEM 25 REAR SCREW.

■ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON
AMP-O-LECTRIC 1-471273-3
~~AMP-O-MATIC~~ MECH FEED ~~[illegible]~~

SERIAL NO. | DATE SHIPPED

CUSTOMER NAME AND ADDRESS

APPLICATOR NUMBER | REV. E | 671737-4

DIST. 4

DESIGNED 1/8/68

CHK'D. 1-8-68

APP'D. 1-8-68

SHEET 1 OF 2

OK