


Left Side

Connector(s): MT-RJ (No Pins)
 Mode: MM
 Housing Color: Black
 Geom. Spec: 115-1215



Fiber Path

Fiber A - - B
 Fiber B - - A

Notes:

- 1 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
- 2 Label 2 will not be present on any cable assembly less than 5 meters long.
- 3 Includes dust caps (not shown on print).

Right Side

Connector(s): SC-Duplex
 Mode: MM
 Housing Color: Beige
 Geom. Spec: N/A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS. IT MAY NOT BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC
 CE
 DIST
 16

B	Rev Per EC#	06-021324	9/6/2006	-	MK	
P	LTR	REVISION RECORD	DATE	DN	APVD	

DIMENSIONS: meters	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 P.L.C. ± .
	1 P.L.C. ± .
	2 P.L.C. ± .
	3 P.L.C. ± .
	4 P.L.C. ± .

DRN Cable Assy Configurator	MATERIAL -	HEAT TREAT -
CHK Michael Kepko	Tyco Electronics, Inc. Harrisburg, PA 17105-3608	
APVD Michael Kepko		
NAME FO C/A - 2 fiber, 62.5/125, OFNR (Riser) jacket, MT-RJ (No Pins) to SC-Duplex		
SCALE NTS	SIZE A2	DRAWING NO C- 6278028
SHEET 1 of 3	REV B	

Customer Print

Restricted to: General Release

USED ON

THIS DRAWING IS A CONTROLLED DOCUMENT.

Part #	L (meters)	L (feet)	MT-RJ (No Pins), Black		SC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-6278028-1	0.950 - 1.050	3.11 - 3.44	0.5	20	0.5	-
0-6278028-2	1.950 - 2.050	6.39 - 6.72	0.5	20	0.5	-
0-6278028-3	2.950 - 3.050	9.67 - 10.00	0.5	20	0.5	-
0-6278028-4	3.920 - 4.080	12.86 - 13.38	0.51	20	0.51	-
0-6278028-5	4.920 - 5.080	16.14 - 16.66	0.51	20	0.51	-
0-6278028-6	5.920 - 6.080	19.42 - 19.94	0.51	20	0.51	-
0-6278028-7	6.920 - 7.080	22.70 - 23.22	0.51	20	0.51	-
0-6278028-8	7.920 - 8.080	25.98 - 26.50	0.51	20	0.51	-
0-6278028-9	8.850 - 9.150	29.03 - 30.01	0.51	20	0.51	-
1-6278028-0	9.850 - 10.150	32.31 - 33.30	0.52	20	0.52	-
1-6278028-1	10.850 - 11.150	35.59 - 36.58	0.52	20	0.52	-
1-6278028-2	11.850 - 12.150	38.87 - 39.86	0.52	20	0.52	-
1-6278028-3	12.850 - 13.150	42.15 - 43.14	0.52	20	0.52	-
1-6278028-4	13.850 - 14.150	45.43 - 46.42	0.52	20	0.52	-
1-6278028-5	14.850 - 15.150	48.72 - 49.70	0.52	20	0.52	-
1-6278028-6	15.840 - 16.160	51.96 - 53.01	0.52	20	0.52	-
1-6278028-7	16.830 - 17.170	55.21 - 56.33	0.53	20	0.53	-
1-6278028-8	17.820 - 18.180	58.46 - 59.64	0.53	20	0.53	-
1-6278028-9	18.810 - 19.190	61.71 - 62.95	0.53	20	0.53	-
2-6278028-0	19.800 - 20.200	64.96 - 66.27	0.53	20	0.53	-
2-6278028-1	20.790 - 21.210	68.20 - 69.58	0.53	20	0.53	-
2-6278028-2	21.780 - 22.220	71.45 - 72.90	0.53	20	0.53	-
2-6278028-3	22.770 - 23.230	74.70 - 76.21	0.53	20	0.53	-
2-6278028-4	23.760 - 24.240	77.95 - 79.52	0.54	20	0.54	-
2-6278028-5	24.750 - 25.250	81.20 - 82.84	0.54	20	0.54	-
2-6278028-6	25.740 - 26.260	84.44 - 86.15	0.54	20	0.54	-
2-6278028-7	26.730 - 27.270	87.69 - 89.46	0.54	20	0.54	-
2-6278028-8	27.720 - 28.280	90.94 - 92.78	0.54	20	0.54	-
2-6278028-9	28.710 - 29.290	94.19 - 96.09	0.54	20	0.54	-
3-6278028-0	29.700 - 30.300	97.44 - 99.40	0.55	20	0.55	-
3-6278028-1	30.690 - 31.310	100.68 - 102.72	0.55	20	0.55	-
3-6278028-2	31.680 - 32.320	103.93 - 106.03	0.55	20	0.55	-
3-6278028-3	32.670 - 33.330	107.18 - 109.35	0.55	20	0.55	-
3-6278028-4	33.660 - 34.340	110.43 - 112.66	0.55	20	0.55	-
3-6278028-5	34.650 - 35.350	113.68 - 115.97	0.55	20	0.55	-
3-6278028-6	35.640 - 36.360	116.92 - 119.29	0.55	20	0.55	-
3-6278028-7	36.630 - 37.370	120.17 - 122.60	0.56	20	0.56	-
3-6278028-8	37.620 - 38.380	123.42 - 125.91	0.56	20	0.56	-
3-6278028-9	38.610 - 39.390	126.67 - 129.23	0.56	20	0.56	-
4-6278028-0	39.600 - 40.400	129.92 - 132.54	0.56	20	0.56	-
5-6278028-0	49.500 - 50.500	162.40 - 165.68	0.58	20	0.58	-
9-6278028-7	2.450 - 2.550	8.03 - 8.36	0.5	20	0.5	-

Qty	U of M	Description	Item No.
1	piece	HOUSING, CONN, MT-RJ.BLACK	1
1	piece	DUST COVER, MT-RJ	2
1	piece	SPRING, MT-RJ, 3.8 DESIGN	3
1	piece	PIN KEEPER, 3.8MM	4
1	piece	MT-RJ, SPRING PUSH, UNIVERSAL	5
1	piece	CRIMP EYELET, MT-RJ	6
2	piece	LC, SC, FC Straight Boot, Beige	7
1	piece	MT-RJ FERRULE, THERMOPLAST,MM	8
2	piece	SC Simplex Housing, Beige	9
2	piece	2.5mm ferrule cover	10
AR	meter	2 fiber, 62.5/125, 1.8 mm, Twinzip, Orange, OFNR (Riser)	11
1	piece	MT-RJ TwinZip Bend Limiting Boot, Beige	12
2	piece	SC Duplex Clip	13
2	piece	Eyelet/Shrink tube assembly - White	14
2	piece	CONN SUBASSY, MM, SC 1.6MM	15
2	piece	Trace Label	16

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS TO BE USED ONLY BY THE PERSONNEL TO WHOM IT IS ISSUED AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC
CE
DIST
16

Rev Per	EC#	06-021324	9/6/2006	-	MK
P	LTR	REVISION RECORD	DATE	DN	APVD

Customer Print

DIENSIONS: meters

TOLERANCES UNLESS OTHERWISE SPECIFIED:

9 P.L.C. ± .005
 1 P.L.C. ± .005
 2 P.L.C. ± .005
 3 P.L.C. ± .005
 4 P.L.C. ± .005

DIN Cable Assy Configurator

MATERIAL - HEAT TREAT -

OK Michael Kepko

APVD Michael Kepko

NAME FO C/A - 2 fiber, 62.5/125, OFNR (Riser) jacket, MT-RJ (No Pins) to SC-Duplex

SCALE NTS SIZE A2 DRAWING NO C- 6278028 SHEET 2 of 3 REV B

AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608

8 7 6 5 4 3 2 1

Restricted to: General Release

Part #	L (meters)	L (feet)	MT-RJ (No Pins), Black		SC-Duplex, Beige	
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
9-6278028-8	1.450 - 1.550	4.75 - 5.08	0.5	20	0.5	-
9-6278028-9	0.470 - 0.530	1.54 - 1.73	0.5	20	0.5	-

THIS DRAWING IS A CONTROLLED DOCUMENT.

Label 1

Per specification 107-1645-1

			Trace # - Bar Code
XXXXXXXXXXXXXXXX			Trace # - Human Readable
Tyco logo	Made in XXXX	X-XXXXXXXX-X	Part Number
			Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1

			Trace # - Bar Code
XXXXXXXXXXXXXXXX			Trace # - Human Readable
Tyco logo	Made in XXXX	X-XXXXXXXX-X	Part Number
			Country of Origin

This label is used on all lengths on this drawing.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS AFFILIATES. IT MAY NOT BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

LOC
CE
DIST
16

B	Rev Per EC#	06-021324	9/6/2006	-	MK		
P	LTR	REVISION RECORD	DATE	DIN	APVD		

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
meters	0 PLC ± .
	1 PLC ± .
	2 PLC ± .
	3 PLC ± .
	4 PLC ± .



Customer Print

DIN	Cable Assy Configurator	MATERIAL	-	HEAT TREAT	-
CHK	Michael Kepko				
APVD	Michael Kepko				
NAME	FO C/A - 2 fiber, 62.5/125, OFNR (Riser) jacket, MT-RJ (No Pins) to SC-Duplex				
SCALE	SIZE	DRAWING NO	SHEET	REV	
NTS	A2	C- 6278028	3 of 3	B	

AMP Tyco Electronics, Inc.
Harrisburg, PA 17105-3608