



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TM500

Internet Office 500VA Low-profile Standby 120V UPS

Highlights

- 6 outlets (3 UPS/surge, 3 surge-only)
- Built-in RJ11 jacks provide complete modem/fax surge protection
- Under-monitor design supports virtually any monitor
- \$150,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)



Description

Tripp Lite's space-saving TM500 Under-Monitor UPS System provides complete power protection for your entire computer set-up, even power hungry peripherals. 500 VA of battery backup maintains your Internet connection, allowing you to work online through short blackouts or safely shut down during longer ones. Unique design features 6 outlets (3 UPS & surge + 3 surge-only), individually switched outlets and diagnostic LEDs. Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment. A 6-ft. telephone cord is also included. \$150,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico, & Canada Only).

Package Includes

- TM500 UPS System
- 6-ft. telephone cord
- Warranty information
- Instruction manual

Features

- 500 VA output power rating (300 watts)
- Up to 30 minutes typical backup time
- 6 protected outlets (3 UPS & surge + 3 surge-only); 6 ft. cord
- Unique space-saving, under-monitor console design
- Built-in RJ11 jacks prevent surges from damaging your modem/fax equipment; 6 ft. telephone cord included
- Complete surge protection and EMI/RFI noise filtering
- \$150,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico. & Canada Only) —
- Master switch and 4 auxiliary switches give you control over multiple pieces of your equipment
- 4 diagnostic LEDs indicate AC Present, line fault, On Battery & Battery Low/Replace

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	500

Output Watt Capacity (watts)	300
Nominal Output Voltage(s) Supported	120V
Frequency compatibility	60 Hz
Output voltage regulation (Battery mode)	+/- 5%
Built-in UPS output receptacles	6 5-15R outlet(s)
Surge suppression only outlets	3 UPS outlets, 3 surge-only outlets
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	PWM sine wave
INPUT	
Rated input current (at maximum load)	15A
Nominal Input Voltage(s) Supported	120V AC
UPS input connection type	5-15P
UPS Input cord length (ft.)	6
UPS Input cord length (m)	1.8
Recommended Electrical Service	15A 120V
BATTERY	
Full load runtime (minutes)	6 min. (300w)
Half load runtime (minutes)	17 min. (150w)
DC system voltage (VDC)	12
Battery recharge rate (included batteries)	Less than 4 hours from 10% to 90%
LEDS ALARMS & SWITCHES	
LED Indicators	Front panel LEDs indicate line power status, battery power status and battery low/replace status
Alarms	Audible alarm indicates power-failure
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation, plus 4 switches control individual output receptacles
SURGE / NOISE SUPPRESSION	
UPS AC suppression joule rating	480
UPS AC suppression response time	Instantaneous
UPS Dataline suppression	1 line TEL/DSL (1 in / 1 out)
EMI / RFI AC noise suppression	Yes

UPC Codes	
Unit Carton UPC#	037332031662
PHYSICAL	
Installation form factors supported with included accessories	Under-monitor console
Primary form factor	Under Monitor
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	2 x 13.5 x 12.5
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	5.1 x 34.3 x 31.8
UPS / Power Module weight (lbs)	11.7
UPS / Power Module weight (kg)	5.3
UPS Shipping dimensions (height x width x depth / inches)	4 x 15 x 16
UPS Shipping dimensions (height x width x depth / cm)	10.2 x 38.1 x 40.6
Shipping weight (lbs)	12
Shipping weight (kg)	5.4
UPS housing material	PVC
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	65.1
Battery mode BTU / hr. (full load)	88.7
LINE / BATTERY TRANSFER	
Transfer time	2-4 milliseconds
Low voltage transfer to battery power (setpoint)	101
SPECIAL FEATURES	
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico)

WARRANTY

Product Warranty Period (Worldwide)	2-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$150,000 Ultimate Lifetime Insurance

Related Items**Optional Products**

Related Model	Description	Qty.
WEXT5-INTERNET	5-Year Extended Warranty - For Internet Office, AVR and ECO Series UPS Systems	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=12.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.