


040 Series (Standard) (Continued)

**Receptacle Contacts
 (For Plug Housing)**
Material and Finish:

KLF-5, pre-tinned or selective gold plated




Wire Range AWG	Wire Range mm ²	Wire Ins. Diameter	Finish	Part No. of Receptacle Contact		Hand Tool No.
				Strip Form	Loose Piece	
24-20*	0.2~0.56	1.1~1.4 .043~.055	Pre-tinned	175180-1	—	—
			Sel. gold	175180-2	—	—
20-14**	0.56~2.09	1.4~2.0 .055~.079	Pre-tinned	173681-1	175062-1	911738-1
			Sel. gold	173681-2	175062-2	(408-417J)
		2.0~2.9 .079~.114	Pre-tinned	173708-1	175081-1	911771-1
			Sel. gold	173708-2	175081-2	(408-422J)

*040 Series for signal circuit. (Extraction tool No. 755430-1/IS-288J)

**070 Series for signal circuit. (Extraction tool No. 755430-2/IS-287J)

**Tab Contacts
 (For Cap Housing)**
Material and Finish:

Pre-tinned brass



Wire Range AWG	Wire Range mm ²	Wire Ins. Diameter	Finish	Part No. of Tab Contact		Hand Tool No.
				Strip Form	Loose Piece	
24-20	0.2~0.56	1.4~2.0 .055~.079	Pre-tinned	173682-1	175063-1	911738-2 (408-417J)