



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDU6K

### Power Distribution Unit (PDU) - Accessory adds additional outlet types to dual voltage UPS System

#### Highlights

- 8 outlet PDU system adds 240 and 120V output receptacles to select dual voltage 240/120V UPS systems
- Includes 4 ft. cord with L14-30 plug
- Input plug supports hardwire input connection
- Supports installation in 2U rackmount, wallmount and under-counter applications

#### Description

Tripp Lite's PDU6K AC power distribution unit offers 24 amp, 240/120V capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 2U rackmount installation. Detachable flanges allow user configuration in dozens of potential mounting schemes. Includes 8 outlets total (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R), with NEMA L14-30P input plug. 4 ft. AC input cord.

PLUG/OUTLETS: Input: NEMA L14-30P/Output: 1 L5-30, 1 L5-20, 2 L6-30, 2 L6-20, 2 6-20R

ELECTRICAL: 240V AC input, 240/120V AC output

FORMAT: Supports 19 in. rackmount (2U), wallmount and under-counter

#### Applications

- Multi-outlet, dual voltage power distribution unit is the ideal means of adding additional types of plug in connections to the output of 240/120 dual voltage UPS systems.

#### Package Includes

- PDU6K rackmount power strip
- Instruction manual

#### Features

- Corded AC power distribution unit with 8 output receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in 2U format
- 4 120V and 4 240V output receptacles (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R)
- 4 ft. AC cord with L14-30 plug-in connection
- Removable plug enables hardwire input connection

#### Specifications

OUTPUT	
Circuit Breaker (amps)	20
Overload protection	20A resettable double pole breaker
Outlet quantity / type	8 outlets (120V: 1 L5-30R, 1 L5-20R, 2 Nema 6-20R / 240V: 2 L6-30R, 2 L6-20R)
INPUT	

<b>Input connection type</b>	Nema L14-30 input plug, removable for 4 wire hardwire installation
<b>Input cord length (ft.)</b>	4
<b>Input cord length (m)</b>	1.2
<b>Voltage compatibility (VAC)</b>	240
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	8
<b>Shipping weight (kg)</b>	3.6
<b>Unit Dimensions (HWD/in)</b>	3.5 x 17.25 x 3.75
<b>Unit Dimensions (HWD/cm)</b>	8.9 x 43.8 x 9.5
<b>Shipping Dimensions (HWD/in)</b>	6.5 x 18.25 x 8.25
<b>Shipping Dimensions (HWD/cm)</b>	16.5 x 46.4 x 21
<b>Unit weight (lbs)</b>	6.25
<b>Unit weight (kg)</b>	2.8
<b>Material of construction</b>	Sheet metal
<b>Mounting accessories included</b>	Recessed rackmount installation brackets
<b>Receptacle Color</b>	Black
<b>AC line cord color</b>	Black
<b>Form factors supported</b>	2U rackmount, wallmount, under-counter
<b>CERTIFICATIONS</b>	
<b>Approvals</b>	UL1778 (USA), cUL (Canada), NOM (Mexico)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=2653](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=2653).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.