

EV INMP401: Bottom Port Analog MEMS Microphone Evaluation Board

GENERAL DESCRIPTION

The EV_INMP401 is a simple evaluation board that allows quick evaluation of the performance of the ADMP401 bottom-ported analog output omnidirectional microphone. The EV_INMP401 uses a 3.5 mm jack for connection to an amplifier or a sound card input. An interconnect cable is provided with the evaluation board.

A single CR1220 3 V Lithium battery powers the INMP401. The battery is included with the board. Note that the power is always on when the battery is inserted. Disconnect the battery when not using the evaluation board to extend battery life.

EVALUATION BOARD CIRCUIT

The schematic of the EV_INMP401 is shown in Figure 1. See the INMP401 data sheet for a complete description and specifications of the microphone. The evaluation board includes a bypass capacitor, C1, a DC-blocking capacitor, C2, a battery holder, BT1, and an output jack, J1.




Figure 1. Evaluation Board Schematic




Figure 2. Evaluation Board Photo



Compliance Declaration Disclaimer:

InvenSense believes this compliance information to be correct but cannot guarantee accuracy or completeness. Conformity documents for the above component constitutes are on file. InvenSense subcontracts manufacturing and the information contained herein is based on data received from vendors and suppliers, which has not been validated by InvenSense.

Environmental Declaration Disclaimer:

InvenSense believes this environmental information to be correct but cannot guarantee accuracy or completeness. Conformity documents for the above component constitutes are on file. InvenSense subcontracts manufacturing and the information contained herein is based on data received from vendors and suppliers, which has not been validated by InvenSense.

This information furnished by InvenSense is believed to be accurate and reliable. However, no responsibility is assumed by InvenSense for its use, or for any infringements of patents or other rights of third parties that may result from its use. Specifications are subject to change without notice. InvenSense reserves the right to make changes to this product, including its circuits and software, in order to improve its design and/or performance, without prior notice. InvenSense makes no warranties, neither expressed nor implied, regarding the information and specifications contained in this document. InvenSense assumes no responsibility for any claims or damages arising from information contained in this document, or from the use of products and services detailed therein. This includes, but is not limited to, claims or damages based on the infringement of patents, copyrights, mask work and/or other intellectual property rights.

Certain intellectual property owned by InvenSense and described in this document is patent protected. No license is granted by implication or otherwise under any patent or patent rights of InvenSense. This publication supersedes and replaces all information previously supplied. Trademarks that are registered trademarks are the property of their respective companies. InvenSense sensors should not be used or sold in the development, storage, production or utilization of any conventional or mass-destructive weapons or for any other weapons or life threatening applications, as well as in any other life critical applications such as medical equipment, transportation, aerospace and nuclear instruments, undersea equipment, power plant equipment, disaster prevention and crime prevention equipment.

©2014 InvenSense, Inc. All rights reserved. InvenSense, MotionTracking, MotionProcessing, MotionProcessor, MotionFusion, MotionApps, DMP, and the InvenSense logo are trademarks of InvenSense, Inc. Other company and product names may be trademarks of the respective companies with which they are associated.



©2014 InvenSense, Inc. All rights reserved.

Document Number: UG-126--00
Revision: 1.0