4850, 4-pole, Line Socket, solder terminal, DIN Plug/Socket





Description

- Solder terminal :

for cable mounting

- DIN Plug: 4-pole , straight


Technical Data


iconnical Bata			
Diameter	9.0 mm	Allowable Operation Tempe-	-20 °C to 70 °C
Number of Poles	4-pole	rature	
Ratings DC	2A / 12VDC	Terminal	solder terminal silver plated
Ratings AC	1 A / 100 VAC	Lifetime	5000 Insertions
Dielectric Strength	250 VAC		
Insulation Resistance	>50 MΩ @ 250VDC		

RoHS

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in General Product Information

Dimensions







4850.3400

Cable diameter max. 5.0 mm

All Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DIN Plug/Socket	9.0	4-pole	solder terminal	4850.3400

Availability for all products can be searched real-time:http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Mating Inlets/Plugs

Category / Description



DIN Plug/Socket Overview complete

4850, 4-pole, Plug, solder terminal, DIN Plug/Socket

DIN Plug/Socket further types to 4850.3400

4850.1410

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.