



AMP
 WIRE RANGE
 2 AWG
 STRANDED

METRIC
 DIMENSIONS LISTED IN mm [INCHES]

1. TONGUE MATERIAL THK 1.45±0.08 [.057±.003] FOR 11.89 [.468] MAX WIRE INS DIA

**AMP INCORPORATED
 CUSTOMER SERVICE SYSTEMS**

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111
FOR ORDER ENTRY	1-800-526-5142

MAX RECOMMENDED OPERATING TEMPERATURE:
105°C

VOLTAGE RATING:
-

CIRCULAR MIL AREA:
26.7-42.4mm² [52,600-83,700] STRANDED

MS25036-127 CLASS 2	-	LOOSE PC	324054
MILITARY P/N & CLASS	QTY	PACKAGE TYPE	PART NO
DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN ENGLISH TOLERANCES ON: 2 PLC DEC ± 0.20(.008) 3 PLC DEC ± - ANGLES ± -	DR 6-21-93 S.S. BOULDEN CHK 6-21-93 R. HERSEY APPD 6-21-93 B. BARE APPD 6-21-93 H. ELLIS	AMP AMP Incorporated Harrisburg, PA 17105-3608	
MATERIAL COPPER PER ASTM B-152 NYLON (MIL-N-20693) TYPE 1 COLOR: RED	PRODUCT SPEC	NAME TERMINAL, RING TONGUE, TERMINYL WIRE SIZE: 2 AWG	
FINISH TIN PLATE PER MIL-T-10727	APPLICATION SPEC	SIZE B	CAGE CODE 00779
	WEIGHT	DRAWING NO C-324054	
		SCALE NTS	SHEET 1 OF 1