


NOTES:

1. GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS.
2. BASE MATERIAL: BRASS, NICKEL PLATED.
3. LAMPS TO BE 100% AGED FOR EQUIVALENT OF TEN HOURS AT RATED VOLTAGE.
4. LAMPS TO BE DIESUNK WITH "JKL" AND NUMBER (EX: JKL 8270).
5. FINAL INSPECTION PER MIL. STD. 105D TO AN AQL OF 2.5 (NOTE: AS15 AND AS10 LAMPS WILL BE 100% INSPECTED FOR MSCP AND AMPERAGE).

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
8270	5.0	.115	.150	1.89	40,000	C-2R

		METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
		DRAWN BY		APPVD BY DATE		SIZE	FSCM NO.	DRAWING NO.		TITLE
		L. WENGSTROM		BW 4/4/00		A	55335			T-3/4 STANDARD MICRO MIDGET FLANGE
RELEASE & CANCEL 7122, 8913, 6183, 8828		4/4/00		- CAD DRAWING -		SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
REV. NO.		DESCRIPTION/ECO NUMBER		MANUAL REVISIONS NOT PERMITTED		NONE	4/4/00			1 OF 1