

UL® CS® HSTTPN Crystal Clear PVC Heat Shrink



- Low shrink temperature (store below 90°F) to speed installation
- Crystal clear material ensures easy to read labels and splice inspections
- Mil Spec: AMS-DTL-23053/2 Class 2
- Highly flame retardant product manufactured from a material that is rated UL 224 VW-1
- Shrink ratio of 2:1 insulates a wide range of diameters and irregular shapes



| Part Number | Nominal Diameter | | Min. Expanded I.D. | | Max. Recovered I.D. | | Nominal Recovered Wall Thickness | | Length | | Length Per Reel | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-----------------|------------------|------|--------------------|------|---------------------|------|----------------------------------|-----|--------|-------|-----------------|------|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | In. | mm | Ft. | m | | |
| HSTTPN50-438-L | 0.46 | 11.7 | 0.46 | 11.7 | 0.25 | 6.4 | 0.022 | 0.6 | 4.38 | 111.3 | — | — | 50 | 500 |
| HSTTPN50-713-Q | 0.46 | 11.7 | 0.46 | 11.7 | 0.25 | 6.4 | 0.022 | 0.6 | 7.13 | 181.1 | — | — | 25 | 250 |
| HSTTPN62-750-Q | 0.56 | 14.3 | 0.56 | 14.3 | 0.31 | 8.0 | 0.027 | 0.7 | 7.50 | 190.5 | — | — | 25 | 250 |
| HSTTPN75-775-Q | 0.70 | 17.7 | 0.70 | 17.7 | 0.38 | 9.5 | 0.027 | 0.7 | 7.75 | 196.9 | — | — | 25 | 250 |
| HSTTPN100-775-Q | 0.90 | 22.9 | 0.90 | 22.9 | 0.50 | 12.7 | 0.030 | 0.8 | 7.75 | 196.9 | — | — | 25 | 250 |
| HSTTPN150-925-X | 1.40 | 35.4 | 1.40 | 35.4 | 0.75 | 19.1 | 0.030 | 0.8 | 9.25 | 235.0 | — | — | 10 | 100 |
| HSTTPN200-950-X | 1.80 | 45.7 | 1.80 | 45.7 | 1.00 | 25.4 | 0.039 | 1.0 | 9.50 | 241.3 | — | — | 10 | 100 |
| HSTTPN50-CC | 0.46 | 11.7 | 0.46 | 11.7 | 0.25 | 6.4 | 0.022 | 0.6 | — | — | 100 | 30.5 | — | — |
| HSTTPN62-CC | 0.56 | 14.3 | 0.56 | 14.3 | 0.31 | 8.0 | 0.027 | 0.7 | — | — | 100 | 30.5 | — | — |
| HSTTPN75-CC | 0.70 | 17.7 | 0.70 | 17.7 | 0.38 | 9.5 | 0.027 | 0.7 | — | — | 100 | 30.5 | — | — |
| HSTTPN100-CC | 0.90 | 22.9 | 0.90 | 22.9 | 0.50 | 12.7 | 0.030 | 0.8 | — | — | 100 | 30.5 | — | — |
| HSTTPN150-CC | 1.40 | 35.4 | 1.40 | 35.4 | 0.75 | 19.1 | 0.030 | 0.8 | — | — | 100 | 30.5 | — | — |
| HSTTPN200-CC | 1.80 | 45.7 | 1.80 | 45.7 | 1.00 | 25.4 | 0.039 | 1.0 | — | — | 100 | 30.5 | — | — |

HSTTN Neoprene Heat Shrink

- Applications include insulating, protecting, and color coding wires and cables
- Excellent chemical resistance especially to fuels and oils
- Voltage: 600 V
- Shrink ratio: 2:1
- Mil Spec: AMS-DTL-23053/1 Class 2
- Temperature range: -94°F to 250°F (-70°C to 121°C)
- For dry locations
- Material: Black cross-linked Neoprene



| Part Number | Nominal Diameter | | Min. Expanded I.D. | | Max. Recovered I.D. | | Nominal Recovered Wall Thickness | | Length per Reel | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|------------------|------|--------------------|------|---------------------|------|----------------------------------|-----|-----------------|------|----------------|----------------|
| | In. | mm | In. | mm | In. | mm | In. | mm | Ft. | m | | |
| HSTTN25-CY | 0.250 | 6.4 | 0.250 | 6.4 | 0.143 | 3.6 | 0.035 | 0.9 | 100 | 30.5 | 1 | 2 |
| HSTTN38-CY | 0.375 | 9.5 | 0.375 | 9.5 | 0.211 | 5.4 | 0.040 | 1.0 | 100 | 30.5 | 1 | 2 |
| HSTTN50-CY | 0.500 | 12.7 | 0.500 | 12.7 | 0.286 | 7.3 | 0.048 | 1.2 | 100 | 30.5 | 1 | 2 |
| HSTTN63-CY | 0.625 | 15.9 | 0.625 | 15.9 | 0.357 | 9.1 | 0.052 | 1.3 | 100 | 30.5 | 1 | 2 |
| HSTTN75-CY | 0.750 | 19.1 | 0.750 | 19.1 | 0.428 | 10.9 | 0.057 | 1.5 | 100 | 30.5 | 1 | 2 |
| HSTTN88-CY | 0.875 | 22.2 | 0.875 | 22.2 | 0.500 | 12.7 | 0.065 | 1.7 | 100 | 30.5 | 1 | 2 |
| HSTTN100-CY | 1.00 | 25.4 | 1.00 | 25.4 | 0.570 | 14.5 | 0.070 | 1.8 | 100 | 30.5 | 1 | 2 |
| HSTTN125-CY | 1.25 | 31.8 | 1.25 | 31.8 | 0.714 | 18.1 | 0.087 | 2.2 | 100 | 30.5 | 1 | 2 |
| HSTTN150-CY | 1.50 | 38.1 | 1.50 | 38.1 | 0.857 | 21.8 | 0.095 | 2.4 | 100 | 30.5 | 1 | 2 |
| HSTTN175-CY | 1.75 | 44.5 | 1.75 | 44.5 | 1.00 | 25.4 | 0.107 | 2.7 | 100 | 30.5 | 1 | 1 |
| HSTTN200-QY | 2.00 | 50.8 | 2.00 | 50.8 | 1.14 | 29.0 | 0.110 | 2.8 | 25 | 7.6 | 1 | 2 |
| HSTTN300-QY | 3.00 | 76.2 | 3.00 | 76.2 | 1.71 | 43.4 | 0.125 | 3.8 | 25 | 7.6 | 1 | 2 |

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index