

596-00652

HellermannTyton

Article Number: 596-00652

Description: Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll



Base Data	Local Order Number	596-00652
	Type	PVACDIS-1
	Color	Red (RD)
	Features and benefits	<ul style="list-style-type: none"> • Made with UV-stable inks and materials for durability and weather resistance. • Polyester is resistant to chemicals and solvents and will remain legible in dirty environments. • High abrasion and scuff resistance for high-performance labeling. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
	Quantity Per	reel
	Product Description	HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Printable Solar Label, PV AC RATING LABEL, 1.0" X 3.75", Red
	Short Description	Solar Label, Printable, PHOTOVOLTAIC AC DISCONNECT, 3.75" x 1.0", PET, Red, 50/roll
	Product Dimensions	Width W (Imperial)
Width W (Metric)		95.25mm
Height H (Imperial)		1.0"
Height H (Metric)		25.4mm
Material and Specifications		Material
	Material Shortcut	PET
	Adhesive	Acrylic

596-00652



Material and Specifications	Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055