



NOTES:FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- TEFLON PER MIL-P-19468
- BERYLLIUM COPPER PER QQ-C-530
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- SILVER PL. 200 MIN. THICK OVER COPPER STRIKE

9	COUPLING NUT	NOTE 1	NOTE 4	1	82-2153-6-B
8	GASKET	SILICONE	RED	1	GS-156/8X15
7	RETAINING RING	SUS 304	NATURAL	1	N5000-7-C
6	CONTACT BODY	NOTE 1	NOTE 4	1	82-2849
5	BUSHING	NOTE 1	NOTE 4	1	82-718
4	INSULATOR	NOTE 2	NATURAL	1	82-10349-2#B
3	INSULATOR	NOTE 2	NATURAL	1	82-10349-1#B
2	CONTACT	NOTE 3	NOTE 5	1	82-10350
1	BODY SUB-ASS'Y	NOTE 1	NOTE 4	1	82-11365
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	
SCALE	3/1	ISSUE	D

PART NO.	
APPROVED	DATE
CHECKED	DATE
DRAWN	DATE
FILE NO. F:\DWG\CNPD\82\98-DSZ	

<b>Amphenol</b>	
Danbury,CT,USA-Tainan,Taiwan-Shenzhen,China	
TITLE	TYPE 'N' ADAPTOR RIGHT ANGLE UG-27B/U
DRAWING NO.	82-98
ITEM NO.	82-98